

# TRUCK MOUNTED FORKLIFTS



+351 251 030 411

hugo.malheiro@mldglobal.eu

+351 939 125 192



## MODEL MF25D

Engine: YANMAR

Fuel: **Diesel** 

Power: 35 kW at 2200 rpm

Certification: Stage 5

Number of Cylinders: 4 in-line

Hydraulic Working Pressure for Attachments: **180 bar** 

Oil Flow for Attachments:

44 I/min

Operator Noise Level: 84 dB

Seat: Yes

Tyre Type: **Pneumatic** 

Front Wheel Dimensions:

10x16.5 IND 10

Rear Wheel Dimensions:

10x16.5 IND 10

Number of Front / Rear

Wheels: 2/1

**Hydraulic Drive Wheels** 

(Front / Rear): **2** / **1** 

**Travel Speed** 

(loaded / unloaded):

10.60 / 10.70 km/h

Lifting Speed

(loaded / unloaded):

0.26 / 0.24 m/s

Lowering Speed

(loaded / unloaded):

0.38 / 0.24 m/s

Gradeability (loaded /

unloaded): 31% / 32%

Acceleration Time (loaded /

unloaded): 4.10 / 2.60 s

Service Brake: *Hydraulic* 

Transmission Type: **Hydrostatic** 

Fork Carriage ISO 2328

(class/format) A/B: 2A



#### **DIMENSIONS**

Operating Weight: 2750 kg

Weight (loaded) on Front / Rear Axle: 4200 / 1050 kg

Weight (unloaded) on Front / Rear Axle: 1280 / 1470 kg

Capacity: 2500 kg (Q)

Load Centre: 500 mm (c)

Load Distance: 424 mm (x)

Wheelbase: **1629 mm** (y)

Front Axle Width: 2143 mm (b10)

Fork Tilt Forward / Backward:  $7^{\circ}/7^{\circ}$  ( $\alpha/\beta$ )

Maximum Lift Height: 3100 mm (h3)

Cabin Height: 2307 mm (h6)

Seat Height from Ground: **1149 mm** (h7)

Overall Length: **2858 mm** (l1)

Overall Width: 2406 mm (b1)

Ground Clearance: 300 mm (m1)

Fork Dimensions (T x W x L): 40 x 122 x 1200 mm

Fork Carriage Width: 1298 mm (b3)


Distance Between Forks: 1278 mm (b5)

Track Width (Wheel Arms): 1603 mm (b4)

Maximum Reach: 1000 mm (I4)

Aisle Width for 800 x 1200 mm Pallet: 3568 mm (Ast)

Turning Radius: 2592 mm (Wa)





#### **DIMENSIONS**

Operating Weight: 2850 kg

Weight (loaded) on Front / Rear Axle: 4060 / 1290 kg Weight (unloaded) on Front / Rear Axle: 950 / 1900 kg

Capacity: 2500 kg (Q)

Load Centre of Gravity: 600 mm (c)

Load Distance: 248 mm (x)

Wheelbase: **1785 mm** (y)

Front Axle Width: **2143 mm** (b10)

Fork Tilt Forward / Backward:  $12^{\circ}/14^{\circ}$  ( $\alpha/\beta$ )

Maximum Lift Height: 3400 mm (h3)

Cab Height: **2296 mm** (h6)

Seat Height from Ground: **1149 mm** (h7)

Overall Length: **3209 mm** (l1)

Overall Width: 2406 mm (b1)

Ground Clearance: 300 mm (m1)

Fork Dimensions (T x W x L): **40 x 122 x 1200 mm** 

Fork Carriage Width: **1298 mm** (b3)


Distance Between Forks: 1278 mm (b5)


Track Width (Wheel Arms): 1603 mm (b4)

Maximum Reach: 1316 mm (l4)

Aisle Width for 800 x 1200 mm Pallet: 3854 mm (Ast)

Turning Radius: 2700 mm





## MODEL **TMF25D**

Engine: YANMAR

Fuel: **Diesel** 

Power: 35 kW at 2200 rpm

Certification: Stage 5

Number of Cylinders: 4 in-line

Hydraulic Working Pressure for Attachments: **180 bar** 

Oil Flow for Attachments: 44 I/min

Operator Noise Level: 84 dB

Seat: Yes

Tyre Type: **Pneumatic** 

Front Wheel Dimensions:

10x16.5 IND 10

**Rear Wheel Dimensions:** 

10x16.5 IND 10

Number of Front / Rear

Wheels: 2/1

Hydraulic Drive Wheels

(front / rear): 2 / 1

Travel Speed (loaded /

unloaded): 10.60 / 10.70 km/h

Lifting Speed (loaded /

unloaded): 0.26 / 0.24 m/s

Lowering Speed (loaded /

unloaded): 0.38 / 0.24 m/s

Gradeability (loaded /

unloaded): 31% / 32%

Acceleration Time

(loaded / unloaded): 4.10 / 2.60 s

Service Brake: *Hydraulic* 

Transmission Type: **Hydrostatic** 

Fork Carriage ISO 2328

(class/format) A/B: 2A

## **MODEL** MCF25

Engine: YANMAR

Fuel: **Diesel** 

Power: 18 kW 35 kW (optional)

Certification: **Stage 5** 

Hydraulic Working Pressure for Attachments: 180 bar

> **Fuel Tank** Capacity: 50 L

Hydraulic Tank Capacity: 50 L

Travel Speed (loaded / unloaded): 2.2 / 4 km/h

Gradeability (loaded / unloaded): 15% / 15%

Load Centre of Gravity:

600 mm

Service Brake:

Hydraulic

**Transmission Type:** 

Hydrostatic

**Load Capacity:** 

2500 kg


Maximum Lift Height: 3100 mm



#### **DIMENSIONS**

Transport Width: 2325 mm Transport Height: 2540 mm Transport Length: 2950 mm Weight: 3350 kg















TRUCK-MOUNTED **FORKLIFTS** 









